

## Special Features:

- With Double Flushing Ports.
- Suitable with Flanged ,Pancake or Inline diaphragm Seals.
- Available in all Exotic Materials Grades.

## Applications:

- Sandwiched between process flange & Diaphragm Seal.
- Allows material flushing from front Diaphragm through flushing ports.

## Standard Version:

- Flange Size : 2" to 5" as per ANSI B 16.5
- Material : AISI 316 SS
- Number of Ports : Two
- Port Connection: 1/4" NPT (F) with male plug
- Sealing face : Raised Face



## HOW TO ORDER

### BASIC MODEL

### FLUSHING RING MATERIAL

<b>KM</b>	AISI 316L SS	<b>KV</b>	CARBON STEEL	<b>KX</b>	TITANIUM
<b>KY</b>	HASTELLOY C	<b>KW</b>	MONEL	<b>CT</b>	ANSI 316 SS (Standard)
<b>UW</b>	INCONEL 625	<b>UN</b>	SUPER DUPLEX	<b>TE</b>	UNS S31254

### FLUSHING PORTS ( WITH TWO MALE PLUGS)

<b>VF</b>	1/4"NPT (F) Standard	<b>VD</b>	1/2"NPT(F)
-----------	----------------------	-----------	------------

### SEALING FACE

<b>A2</b>	RAISED FACE	<b>A3</b>	FLAT FACE	<b>A5</b>	RING JOINT (RTJ,RJ)
-----------	-------------	-----------	-----------	-----------	---------------------

**Note :** Other Sealing face can be provided on request.Please specify in notes.

### OPTIONS

<b>GH</b>	Material Test Certificate**
-----------	-----------------------------

AC-04

XX

XX

XX

XX

**Ordering Example: AC-04-XX-XX-XX-XX**