

## Special Features:

PTFE adjustable packing installed below operating threads to prevent media Contamination or Lubricant washout of operating threads spindle for longer durable operation with air vent hole (Optional)



## Applications:

- Hydraulic Machines
- Compressors
- Process Plants
- Gases & Non Crystallized Liquids
- Clean Air

## Standard Version:

- Body: AISI 316 SS
- Handle: AISI 316 SS
- Working Temperature: Up to 180°C
- Gasket Seal: PTFE Nominal
- Pressure: 100 kg/cm<sup>2</sup>

### HOW TO ORDER

#### BASIC MODEL

Example

AC-02

#### TYPE

<b>KS</b> 2 WAY-ROUND BAR	<b>KU</b> 3 WAY-ROUND BAR	<b>KT</b> 3 WAY-ROUND BAR	XX
---------------------------	---------------------------	---------------------------	----

#### BODY

<b>KM</b> AISI 316L SS	<b>KV</b> CARBON STEEL	<b>KX</b> TITANIUM	XX
<b>KY</b> HASTELLOY C	<b>KW</b> MONEL	<b>CT</b> AISI 316 SS (Standard)	
<b>CP</b> BRASS			

#### SIZE & END CONNECTION [ INLET X OUTLET]

<b>NF</b> 1/4" (F X F) (Standard)	<b>NI</b> 3/8" (F X F) (Standard)	<b>NL</b> 1/2" (F X F) (Standard)	XX
<b>NG</b> 1/4" (M X F)	<b>NJ</b> 3/8" (M X F)	<b>NM</b> 1/2" (M X F)	
<b>NH</b> 1/4" (M X M)	<b>NK</b> 3/8" (M X M)	<b>NN</b> 1/2" (M X M)	

In case of 3 Way Gauge Cock ,One Connection will be Male & Another Two will be Female.

**Example:NM: 1/2" (M X F) Means 1/2" (M X F X F)**

#### THREAD TYPE

<b>GU</b> BSP	<b>GV</b> NPT	XX
---------------	---------------	----

#### OPTIONAL EXTRAS

<b>GH</b> Material Test Certificate	<b>GI</b> Vent Hole	XX
-------------------------------------	---------------------	----

**Ordering Example: AC-02-XX-XX-XX-XX-XX**